


## Gate Valves

**COMPANY**

**SHIELD FIRE SAFETY & SECURITY LTD**

Unit 3, Endeavour Dr  
 Basildon, SS14 3WF United Kingdom

EX6704



Note: For additional marking information, refer to the [Guide Information Page](#).

*View model for additional information*

Model(s): [SD-NRS175FF-D1](#), [SD-NRS175FF-D1PJ](#), [SD-NRS175FF-PN10](#), [SD-NRS175FF-PN10PJ](#), [SD-NRS175GV](#), [SD-NRS175GV-D](#), [SD-NRS200FF-D](#), [SD-NRS200FF-D1](#), [SD-NRS200FF-D1PJ](#), [SD-NRS200FF-D2](#), [SD-NRS200FF-PN16](#), [SD-NRS200FG-D](#), [SD-NRS200FG-PN16](#), [SD-NRS200FM-D1](#), [SD-NRS200GF-D2](#), [SD-NRS200GG-D](#), [SD-NRS200GG-PN16](#), [SD-NRS200GV-D](#), [SD-NRS200MM-D1](#), [SD-NRS232FF-PN16](#), [SD-NRS232FF-PN16PJ](#), [SD-NRS250FF-D](#), [SD-NRS250FF-D1](#), [SD-NRS250FF-D1PJ](#), [SD-NRS250FF-PN16](#), [SD-NRS250FG-D](#), [SD-NRS250FG-PN16](#), [SD-NRS250FM-D1](#), [SD-NRS250GG-D](#), [SD-NRS250GG-PN16](#), [SD-NRS250GV-D](#), [SD-NRS250MM-D1](#), [SD-NRS300AGF-D2](#), [SD-NRS300AGF-PN16](#), [SD-NRS300AGG-D2](#), [SD-NRS300AGG-PN16](#), [SD-NRS300FF-D](#), [SD-NRS300FF-D2](#), [SD-NRS300FG-D](#), [SD-NRS300FG-PN16](#), [SD-NRS300FJA-D2](#), [SD-NRS300GF-D2](#), [SD-NRS300GG-D](#), [SD-NRS300GG-PN16](#), [SD-NRS300GV-D](#), [SD-NRS300MJA-D2](#), [SD-NRS360FF-D](#), [SD-NRS360FF-PN16](#), [SD-NRS360FF-PIF](#), [SD-NRS360FF-PIFSW](#), [SD-NRS360FF-SW](#), [SD-NRS5FF-PN16](#), [SD-NRS5FG-PN16](#), [SD-NRS5GG-PN16](#), [SD-OSY175FF-D1](#), [SD-OSY175FF-PN10](#), [SD-OSY175GV](#), [SD-OSY175GV-D](#), [SD-OSY200FF-D](#), [SD-OSY200FF-D1](#), [SD-OSY200FF-D2](#), [SD-OSY200FF-PN16](#), [SD-OSY200FG-D](#), [SD-OSY200FG-PN16](#), [SD-OSY200FM-D1](#), [SD-OSY200GG-D](#), [SD-OSY200GG-PN16](#), [SD-OSY200GV-D](#), [SD-OSY200MM-D1](#), [SD-OSY232FF-PN16](#), [SD-OSY250FF-D](#), [SD-OSY250FF-D1](#), [SD-OSY250FF-PN16](#), [SD-OSY250FG-D](#), [SD-OSY250FG-PN16](#), [SD-OSY250FM-D1](#), [SD-OSY250GG-D](#), [SD-OSY250GG-PN16](#), [SD-OSY250GV-D](#), [SD-OSY250MM-D1](#), [SD-OSY300AGF-D2](#), [SD-OSY300AGF-PN16](#), [SD-OSY300AGG-D2](#), [SD-OSY300FF-D](#), [SD-OSY300FF-D2](#), [SD-OSY300FG-D](#), [SD-OSY300FG-PN16](#), [SD-OSY300GF-D2](#), [SD-OSY300GG-D](#), [SD-OSY300GG-PN16](#), [SD-OSY300GV-D](#), [SD-OSY360FF-D](#), [SD-OSY360FF-SW](#), [SD-OSYFF-PN16](#), [SD-OSYFG-PN16](#), [SD-OSYGG-PN16](#)

**O.S. and Y pattern**, Model(s): [SDOSY-T](#)

**Last Updated** on 2024-12-06

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2025 UL LLC."

# Model SD-OSY200FF-D

## Product Description

Resilient Seated Gate Valves. 2 through 24 in. NPS. Valves have a rated working pressure of 200 psi (2070 kPa). Available with the following end connections.

## Product Specification

Model No	Valve Size		End Connection
	in	(mm)	
SD-OSY200FF-D	2, 2 1/2, 3, 4, 6, 8, 10, 12, 14, 16, 18, 20, 24	(50, 65, 80, 100, 150, 200, 250, 300, 350, 400, 450, 500, 600)	Flange x Flange

## Details

<b>Category</b>	Gate Valves, Outside Screw and Yoke
<b>Class of Work</b>	1120 - OS&Y and NRS Gate Valves
<b>Approval Standard</b>	FM 1120, 1130 - Fire Service Water Control Valves (OS&Y and NRS Type Gate Valves)
<b>Certification Type</b>	FM Approved
<b>Listing Country</b>	United Kingdom

## Company

**Shield Fire Safety and Security Ltd**  
 Unit 3 Endeavor Drive, Basildon, Essex, SS14 3WF, United Kingdom  
<http://www.shieldglobal.com>

## Model SD-OSY300FF-D

### Product Description

Resilient Seated Gate Valves. 2 through 12 in. NPS. Valves have a rated working pressure of 300 psi (2070 kPa). Available with the following end connections.

### Product Specification

Model No	Valve Size		End Connection
	in	(mm)	
SD-OSY300FF-D	2, 2 1/2, 3, 4, 6, 8, 10, 12	(50, 65, 80, 100, 150, 200, 250, 300)	Flange x Flange (ANSI, BS, EN, JIS)

## Details

<b>Category</b>	Gate Valves, Outside Screw and Yoke
<b>Class of Work</b>	1120 - OS&Y and NRS Gate Valves
<b>Approval Standard</b>	FM 1120, 1130 - Fire Service Water Control Valves (OS&Y and NRS Type Gate Valves)
<b>Certification Type</b>	FM Approved
<b>Listing Country</b>	United Kingdom

## Company

**Shield Fire Safety and Security Ltd**  
 Unit 3 Endeavor Drive, Basildon, Essex, SS14 3WF, United Kingdom  
<http://www.shieldglobal.com>

# Model SD-OSY300FG-D

## Product Description

Resilient Seated Gate Valves. 2 through 12 in. NPS. Valves have a rated working pressure of 300 psi (2070 kPa). Available with the following end connections.

## Product Specification

Model No	Valve Size		End Connection
	in	(mm)	
SD-OSY300FG-D	2, 2 1/2, 3, 4, 6, 8, 10, 12	(50, 65, 80, 100, 150, 200, 250, 300)	Groove x Flange (AWWA C606 x ASME B16.1)

## Details

<b>Category</b>	Gate Valves, Outside Screw and Yoke
<b>Class of Work</b>	1120 - OS&Y and NRS Gate Valves
<b>Approval Standard</b>	FM 1120, 1130 - Fire Service Water Control Valves (OS&Y and NRS Type Gate Valves)
<b>Certification Type</b>	FM Approved
<b>Listing Country</b>	United Kingdom

## Company

**Shield Fire Safety and Security Ltd**  
 Unit 3 Endeavor Drive, Basildon, Essex, SS14 3WF, United Kingdom  
<http://www.shieldglobal.com>